| Product Safety Data Sheet | Document No. | | |
|---------------------------|---------------------------|--------------|--------|
| | Issue | 01.07 | |
| | Date Last Amended | October 2023 | |
| | Last Amended by | MLN | ocean |
| Document Title | LB8E Lithium Battery PSDS | | SIGNAL |

Product Name: Lithium Battery Pack Type №: LB8E

For use with: RescueME EPIRB1, EPIRB1 Pro

Chemistry: LiMnO₂ **Total Weight:** 51q **Nominal Voltage:** 9V

Construction: The EPIRB1 contains two batteries, each containing three Q-Lite

Industrial Ltd. CR123 cells connected in series. The batteries are

isolated from each other for transportation.

Lithium weight/cell: 0.51g **Total lithium weight/battery:** 1.53g

Section 1 – Manufacturer Information

Manufactured by: Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT9

4NN, United Kingdom

Telephone number: +44 (0)1843 282930

Section 2 - Hazards Identification

This battery module is a self-contained unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

Ingestion: Swallowing the contents of a damaged battery can be harmfulInhalation: Contents of a damaged battery can cause respiratory irritation

Skin Contact: Contents of a damaged battery can cause irritation

Eye Contact: Contents of a damaged battery can cause severe irritation

Section 3 - Ingredients

Important Note: This battery should not be opened or burned. Exposure to the contents may be harmful.

| Material or Ingredient | PEL (OSHA) | TLV (ACGIH) | %/wt. |
|---|------------------------|-------------------------|----------|
| Lithium (CAS# 7439-93-2) | None Established | None established | 2 to 3 |
| Lithium perchlorate (CAS# 7791-03-9) | None Established | None Established | 3 to 4 |
| Carbon (CAS# 7440-44-0) | None Established | None Established | <1.0 |
| Manganese Dioxide (CAS# 1313-13-9) | 5mg/m³ Ceiling (as Mn) | 0.2mg/m³ TWA (as Mn) | 30 to 40 |
| 1,2-Dimethoxyethane (CAS# 110-71-4) | None Established | None Established | 3 to 4 |
| Propylene Carbonate (CAS# 108-32-7) | None Established | None Established 3 to 4 | |

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

| Product Safety Data Sheet | Document No. | | |
|---------------------------|---------------------------|--------------|--------|
| | Issue | 01.07 | |
| | Date Last Amended | October 2023 | |
| | Last Amended by | MLN | ocean |
| Document Title | LB8E Lithium Battery PSDS | | SIGNAL |

| Material or Ingredient | PEL (OSHA) | TLV (ACGIH) | %/wt. |
|-------------------------------------|------------------|------------------|-----------|
| Non Hazardous Components | | | |
| Stainless Steel (CAS#12597-68-1) | None Established | None Established | 25 to 35 |
| Other | None Established | None Established | Remainder |

Section 4 - First Aid Measures

Ingestion: If a battery is swallowed, consult a physician immediately.

If contents come into contact with the mouth, immediately rinse by

plenty of water and consult a physician.

Inhalation: Fumes can cause respiratory irritation. Remove to fresh air and consult

a physician.

Skin Contact: Immediately flush skin with plenty of water. If itch or irritation by

chemical burn persists, consult a physician.

Eye Contact: Immediately flush eye with plenty of water for at least 15 minutes. And

consult a physician immediately.

Section 5 – Fire Fighting Measures

In case of fire involving lithium batteries, flood the area with water or smother with a class D fire extinguishing material suitable for lithium metal. (e.g. Lith-X)

Note: Water may not completely extinguish burning lithium batteries but will keep adjacent batteries cool reducing the risk of the fire spreading. As burning batteries will burn themselves out, flooding with water will control virtually all fires involving lithium batteries. However, the contents of lithium batteries will react with water to release hydrogen gas. In enclosed spaces this can cause an explosive mixture. Use a smothering agent in enclosed spaces which will extinguish burning lithium batteries.

Fire responders should wear self contained breathing apparatus. Burning lithium manganese dioxide batteries produce toxic and corrosive lithium hydroxide fumes.

Section 6 - Accidental Release Measures

Should batteries leak the following actions are recommended.

Ventilation: Keep room containing leaking lithium batteries well ventilated

Respiratory Protection: Avoid exposure to fumes from open or leaking batteries

Eye protection: Wear safety glasses with side shields when handling leaking

batteries

Gloves: Neoprene of natural rubber gloves should be worn when

handling leaking batteries

Storage: Leaking batteries should be stored in a leak proof container

Section 7 - Handling and Storage

Storage: Store in a cool, well ventilated area. Elevated temperature may result

in shortened battery life.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

| Braduct Safaty Data Shoot | Document No. | | |
|---------------------------|---------------------------|--------------|--------|
| | Issue | 01.07 | |
| Product Safety Data Sheet | Date Last Amended | October 2023 | |
| | Last Amended by | MLN | ocean |
| Document Title | LB8E Lithium Battery PSDS | | SIGNAL |

Handling: Never swallow.

Never reverse the positive and negative terminals when mounting.

Never short-circuit the battery.

Never expose to open flame or expose the battery to heat.

Never disassemble.

Never touch liquid that may have leaked out of battery.

Never touch battery for an extended period of time.

Charging: These batteries are not designed for charging. Do not attempt to

recharge the battery. Recharging may result in cell venting or rupture.

Section 8 – Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

| Section 9 - Physical and Chemical Properties | | |
|--|------------------------------|--|
| Boiling Point at 760mm Hg (°C) | Not applicable for this item | |
| Vapour Pressure (mm Hg at 25°C) | Not applicable for this item | |
| Vapour Density | Not applicable for this item | |
| Density (g/cm³) | | |
| Percent volatile by volume (%) | Not applicable for this item | |
| Evaporation Rate | Not applicable for this item | |
| Physical State | Solid | |
| Solubility in water | Not applicable for this item | |
| рН | Not applicable for this item | |
| Appearance and odour | Solid object / no odour | |

Section 10 - Stability and Reactivity

No stability or reactivity issues identified

Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2011/65/EU.

Section 12 – Ecological Information

No ecological issues have been identified for this battery

Section 13 – Disposal Considerations

Dispose of battery module in accordance with applicable local regulations

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

| Product Safety Data Sheet | Document No. | | |
|---------------------------|---------------------------|--------------|--------|
| | Issue | 01.07 | |
| | Date Last Amended | October 2023 | |
| | Last Amended by | MLN | ocean |
| Document Title | LB8E Lithium Battery PSDS | | SIGNAL |

Section 14 - Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria. The Lithium content of the each LB8E battery is less than 2grams. Summary test reports are available from Ocean Signal on request.

This battery module should be transported by air in accordance with the IATA dangerous goods regulations 64th edition, class 9, UN3090, proper name "Lithium metal batteries" and packed according to packing instruction 968 section II (one replacement battery kit only) or section Ib.

When supplied with equipment it is class 9, UN3091, proper name "Lithium metal batteries contained in equipment" and should be packed in accordance with packing instruction 970 section II.

The EPIRB1 can be carried as personal luggage on board aircraft under the conditions of clause 2.3.5.9 of the IATA regulations.

The battery modules may be transported by road under special provision 188 of the ADR.

Section 15 Regulatory Information

No additional regulatory requirements are identified for this battery module.

Section 16 - Other

No information