Product Safety Data Sheet	Document No.	925S-06051	
	Issue	01.12	
	Date Last Amended	October 2024	
	Last Amended by	D.Heath	ocean
Document Title	LB4V Lithium Battery Module PSDS		SIGNAL

Product Name: SafeSea Lithium Battery Module **Type №:** LB4V / 1061

For use with: SafeSea V100 / ACR SR203 GMDSS VHF handheld radio

Chemistry: LiFeS₂ **Total Weight:** 148g **Nominal Voltage:** 3V

Construction: Battery module containing three isolated batteries, each of two

Energizer AA cells connected in series

Lithium weight/cell: ~0.98g Total lithium weight/battery: 1.96g

Section 1 – Manufacturer Information

Manufactured by: Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT9

4NN, United Kingdom

Telephone number: +44 (0)1843 282930

Section 2 - Hazards Identification

This battery module is a sealed unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

Ingestion: Swallowing the contents of a damaged battery can be harmfulInhalation: Contents of a damaged battery can cause respiratory irritation

Skin Contact: Contents of a damaged battery can cause irritation

Eye Contact: Contents of a damaged battery can cause severe irritation

Section 3 – Ingredients

Important Note: This battery module should not be opened or burned. Exposure to the contents may be harmful.

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Lithium (CAS# 7439-93-2)	None Established	None established	<5%
Iron Disulfide (CAS# 1309-36-0)	None Established	None Established	<23%
1,3-Dioxolane (CAS# 646-06-0)	None Established	None Established	<5.5%
Lithium bis- Trifluoromethanesulfonimide (CAS# 90076-65-6)	None Established	None Established	<5.5%
Tetramethahylene Sulfolane (CAS# 126-33-0)	None Established	None Established	<1.5%
Non Hazardous Components			
Steel (CAS#7439-89-6)	None Established	None Established	<20%
Plastic and other	None Established	None Established	Remainder

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06051	
	Issue	01.12	
	Date Last Amended	October 2024	
	Last Amended by	D.Heath	ocean
Document Title	LB4V Lithium Battery Module PSDS		SIGNAL

Section 4 - First Aid Measures

The following advice applies only to damaged battery packs that are leaking.

Ingestion: Seek medical advice. Do not induce vomiting or give food or drink.

Inhalation: Seek medical attention. Provide fresh air

Skin Contact: Remove any contaminated clothing and wash affected areas with soap

and water.

Eye Contact: Seek medical attention. Immediately flush eyes with water for a minimum

of 15minutes. Ensure that both upper and lower eyelids are lifted during

the flushing process.

Section 5 – Fire Fighting Measures

In case of fire involving lithium batteries, flood the area with water or smother with a class D fire extinguishing material suitable for lithium metal. (e.g. Lith-X)

Note: Water may not completely extinguish burning lithium batteries but will keep adjacent batteries cool reducing the risk of the fire spreading. As burning batteries will burn themselves out, flooding with water will control virtually all fires involving lithium batteries. However, the contents of lithium batteries will react with water to release hydrogen gas. In enclosed spaces this can cause an explosive mixture. Use a smothering agent in enclosed spaces which will extinguish burning lithium batteries.

Fire responders should wear self contained breathing apparatus.

Section 6 - Accidental Release Measures

Should batteries leak the following actions are recommended.

Ventilation: Keep room containing leaking lithium batteries well ventilated

Respiratory Protection: Avoid exposure to fumes from open or leaking batteries

Eye protection: Wear safety glasses with side shields when handling leaking

batteries

Gloves: Neoprene of natural rubber gloves should be worn when

handling leaking batteries

Storage: Leaking batteries should be stored in a leak proof container

Section 7 - Handling and Storage

Storage: Store in a cool, well ventilated area. Elevated temperature may result in

shortened battery life.

Handling: Avoid accidentally short-circuiting batteries. Prolonged short-circuiting can

cause the battery temperature to rise and significantly reduce battery

life.

Charging: These batteries are not designed for charging. Do not attempt to

recharge the battery. Recharging may result in cell venting or rupture.

Section 8 - Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06051	
	Issue	01.12	
	Date Last Amended	October 2024	
	Last Amended by	D.Heath	ocean
Document Title	LB4V Lithium Battery Module PSDS		SIGNAL

Section 9 - Physical and Chemical Properties		
Boiling Point at 760mm Hg (°C)	Not applicable for this item	
Vapour Pressure (mm Hg at 25°C)	Not applicable for this item	
Vapour Density	Not applicable for this item	
Density (g/cm³)		
Percent volatile by volume (%)	Not applicable for this item	
Evaporation Rate	Not applicable for this item	
Physical State	Solid	
Solubility in water	Not applicable for this item	
pH	Not applicable for this item	
Appearance and odour	Solid object / no odour	

Section 10 - Stability and Reactivity

No stability or reactivity issues identified

Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2011/65/EU.

Section 12 - Ecological Information

No ecological issues have been identified for this battery

Section 13 – Disposal Considerations

Dispose of battery module in accordance with applicable local regulations

Section 14 – Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria. Summary test reports are available from Ocean Signal on request.

This battery module should be transported by air in accordance with the IATA dangerous goods regulations 65th edition, class 9, UN3090, proper name "Lithium metal batteries" and packed according to packing instruction 968 section Ib.

When supplied with equipment it is class 9, UN3091, proper name "Lithium metal batteries packed with equipment" and should be packed in accordance with packing instruction 969 section II.

The LB4V battery can be carried as personal luggage with the V100 on board aircraft under the conditions of clause 2.3.5.8 of the IATA dangerous goods regulations.

The battery modules may be transported by road under special provision 188 of the ADR and IMDG.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06051	
	Issue	01.12	
	Date Last Amended	October 2024	
	Last Amended by	D.Heath	ocean
Document Title	LB4V Lithium Battery Module PSDS		SIGNAL

Section 15 Regulatory Information

No additional regulatory requirements are identified for this battery module.

Section 16 - Other

No information