

Product Safety Data Sheet	Document No.	925S-06052
	Issue	01.14
	Date Last Amended	January 2026
	Last Amended by	D. Heath
Document Title	RB5V Lithium Battery Module PSDS	



Product Name:	safeSEA Lithium Polymer Battery Module (13.3Wh)	Type №:	RB5V/1062
For use with:	safeSEA V100/ACR SR203(A) GMDSS VHF handheld radio		
Chemistry:	LiCoO ₂ /LiPF ₆	Total Weight:	112g
Construction:	Battery module containing two cells connected in series with protection circuitry		
Lithium weight/cell:	<0.5g	Total lithium weight/battery:	<1.0g

Section 1 – Manufacturer Information

Manufactured by: Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT9 4NN, United Kingdom

Telephone number: +44 (0)1843 282930

Section 2 – Hazards Identification

This battery module is a sealed unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

Ingestion: Swallowing the contents of a damaged battery can be harmful

Inhalation: Contents of a damaged battery can cause respiratory irritation

Skin Contact: Contents of a damaged battery can cause irritation

Eye Contact: Contents of a damaged battery can cause serious damage

Section 3 – Ingredients

Important Note: This battery module should not be opened or burned. Exposure to the contents may be harmful.

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Lithium Cobalt(III) Oxide (CAS# 12190-79-3)	0.1mg/m ³	0.02mg/m ³	<17%
Lithium Hexafluorophosphate (CAS# 21324-40-3)	None Established	None Established	<2%
Ethylene Carbonate (CAS# 96-49-1)	None Established	None Established	<7%
Dimethyl Carbonate (CAS# 616-38-6)	None Established	None Established	
Diethyl Carbonate (CAS# 105-58-8)	None Established	None Established	
Ethyl Acetate (CAS# 141-78-6)	1400mg/m ³	400ppm	

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06052
	Issue	01.14
	Date Last Amended	January 2026
	Last Amended by	D. Heath
Document Title	RB5V Lithium Battery Module PSDS	



Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Non Hazardous Components Steel, Copper, Aluminium, Plastics and other inert materials	None Established	None Established	Remainder

Section 4 – First Aid Measures

- Ingestion:** Seek medical advice. Do not induce vomiting or give food or drink.
- Inhalation:** Seek medical attention. Move to an area of fresh air and ventilate the contaminated area. Give oxygen or artificial respiration if required.
- Skin Contact:** Remove any contaminated clothing and wash affected areas with soap and water for a minimum of 15 minutes. Do not apply grease or ointments.
- Eye Contact:** Seek immediate medical attention. Immediately flush eyes with water for a minimum of 15 minutes. Ensure that both upper and lower eyelids are lifted during the flushing process.

Section 5 – Fire Fighting Measures

In case of fire involving lithium polymer batteries, use CO₂, dry chemical or foam extinguishers. Do not use Type D extinguishers.

Fire responders should wear self contained breathing apparatus.

Section 6 - Accidental Release Measures

Should batteries leak the following actions are recommended.

- Ventilation:** Keep room containing leaking lithium polymer batteries well ventilated
- Respiratory Protection:** Avoid exposure to fumes from open or leaking batteries
- Eye protection:** Wear safety glasses with side shields when handling leaking batteries
- Gloves:** Neoprene or natural rubber gloves should be worn when handling leaking batteries
- Storage:** Leaking batteries should be stored in a leak proof container

Section 7 – Handling and Storage

- Storage:** Store in a cool, well ventilated area. Elevated temperature may result in shortened battery life.
- Handling:** Avoid accidentally short-circuiting batteries. Prolonged short-circuiting can cause the battery temperature to rise and significantly reduce battery life.

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06052
	Issue	01.14
	Date Last Amended	January 2026
	Last Amended by	D. Heath
Document Title	RB5V Lithium Battery Module PSDS	



Charging: These batteries should only be charged using the recommended charger (RC1V). Do not attempt to charge with a charger that is not designed to protect against over charge of lithium polymer batteries. Failure to follow these guidelines may result in the battery exploding.

Section 8 – Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

Section 9 – Physical and Chemical Properties

The following applies only to the battery in its normal state. Only store or discharge the battery within the temperature range -30°C to +70°C. Only charge the battery within the temperature range 0°C to +50°C.

Boiling Point at 760mm Hg (°C)	Not applicable for this item
Vapour Pressure (mm Hg at 25°C)	Not applicable for this item
Vapour Density	Not applicable for this item
Density (g/cm³)	Not applicable for this item
Percent volatile by volume (%)	Not applicable for this item
Evaporation Rate	Not applicable for this item
Physical State	Solid
Solubility in water	Not applicable for this item
pH	Not applicable for this item
Appearance and odour	Solid object / no odour

Section 10 – Stability and Reactivity

No stability or reactivity issues identified. The following precautions should be observed.

- To not heat above 70°C or incinerate.
- Do not deform, mutilate, crush pierce or disassemble.
- Do not short circuit.

Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2011/65/EU.

Section 12 – Ecological Information

No ecological issues have been identified for this battery

Section 13 – Disposal Considerations

Dispose of battery module in accordance with applicable local regulations

Ocean Signal Ltd. has issued this Product Safety Data Sheet to provide user advice on the above listed product(s). The information has been prepared in good faith and is believed to be accurate at the date of preparation. Ocean Signal Ltd. makes no warranty, either express or implied, with respect to this information.

Product Safety Data Sheet	Document No.	925S-06052
	Issue	01.14
	Date Last Amended	January 2026
	Last Amended by	D. Heath
Document Title	RB5V Lithium Battery Module PSDS	



Section 14 – Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria. Summary test reports are available from Ocean Signal on request.

This battery module is class 9, UN3480 (Lithium Ion Battery) and should be transported by air in accordance with the IATA dangerous goods regulations 67th edition, packing instruction 965 Section 1B.

When supplied with equipment it is class 9, UN3481 (Lithium-Ion battery packed with equipment) it should be packed in accordance with packing instruction 966 Section II.

The RB5V with the V100 can be carried as personal luggage on board aircraft under the conditions of clause 2.3.5.8 of the IATA regulations.

The battery modules may be transported by road under special provision 188 of the ADR and IMDG.

Section 15 Regulatory Information

No additional regulatory requirements are identified for this battery module.

Section 16 – Other

No information